

TEC 810

... the power to perform

POWER
ADHESIVES

HEAVY DUTY MID-RANGE GLUE GUN

The **TEC 810** is an industrially rated medium size glue gun that sets completely new standards of comfort and performance. It is available in two versions, one for $1/2$ " glue sticks (**TEC 810-12**) and the other for $5/8$ " glue sticks (**TEC 810-15**).

With its compact design, full hand lever trigger, very fast warm up time of only 2 to 3 minutes, and with an impressive glue output of over $4 1/2$ lbs per hour (depending on formulation), the **TEC 810** will soon establish itself as the world leader in the mid-range section of the market.

The **TEC 810** has several unique features including an illuminated on/off switch, a narrow profile handle with soft grip and an adjustable trigger stroke to accommodate most hand sizes.

The tool has a detachable stand with built-in spanners for the nozzle and trigger adjustment. The front of the tool is both slim and smooth, allowing greater access and making it exceptionally easy to keep clean.

The **TEC 810** is heated by a powerful stainless steel cartridge heater which is controlled by a pre-set thermostat. This thermostat can be easily changed to adjust the set temperature of the tool for the many different types of hotmelt and lowmelt adhesives available.

The **TEC 810-12** dispenses $1/2$ " x 12" high performance **TECBOND** hotmelt glue sticks. The **TEC 810-15** dispenses $5/8$ " x 12" high performance **TECBOND** hotmelt glue sticks, giving a third more output of molten glue from each pull of the trigger.

The **TEC 810** is built to comply with world-wide industrial and electrical safety standards, and is covered by a full one year warranty.



ADVANCED FEATURES



Illuminated on-off switch and detachable base stand incorporating nozzle spanner



Open breach for easy cleaning, and trigger stroke adjustment screw to accommodate any size hand



Full hand lever trigger and narrow profile handle with soft feel grip



Easy change temperature thermostats, to suit different types of hotmelt and lowmelt

SPECIFICATION

VOLTAGE	230V OR 110 - 120V 50-60HZ
HEATER	TEC 810-12 250W & TEC 810-15 300W High performance stainless steel cartridge
TEMP CONTROL	Preset Thermostat (fitted with 380F) with safety thermal fuse. Other easy change thermostat available: 270°F 420°F
WEIGHT	1 lb
POWER CABLE	6FT 3 core rubber sheathed cable with plug fitted, UK, European, Australian, Swiss & USA, versions available.
MELT RATE	Over 4 1/2 lbs/hr depending on adhesive & temperature
ADHESIVE SIZE	TECBOND 1/2" Glue Stick TECBOND 5/8" Glue Stick

OPTIONAL NOZZLES Both guns are supplied fitted with a one-piece one hole nozzle with 0.079" orifice. (810-12 part number MDJ010) (810-15 part number ADJ009) optional nozzle caps are available for specialised purposes and to speed up adhesive application.



1 2 3 4 5

REF	PART NO	TYPE	DESCRIPTION
1	ANZ999	Adaptor	This part is needed to use 2,3 & 5 caps
2	MNZ013	2 Hole	2 parallel adhesive line 3/8" apart
3	MNZ027	3 Hole	3 parallel adhesive lines 1/4" apart
4	ADJ004	Slotted Spreader	Allows a 1/2" wide spread of glue
5	PA5032	L. Nozzle	Fast full overlap carton sealing



OPTIONAL ACCESSORIES



SB/1200 Spring Balance with a maximum extended cord length of 5' 3" designed to minimise operator fatigue. It also increases productivity and reduces the

chance of accidental damage to the applicator.



TEC Optional metal stand Part No MDC009 ideal for use on work surface or wall mounted.



TECBOND high performance 1/2" & 5/8" adhesive sticks, specially designed for use in the TEC 810-12 & TEC 810-15, available to bond virtually any material. The range provides a variety of setting times, heat resistances, and viscosities to suit every application. Also available in 1/2" size only coloured and glitter glue sticks for that extra creativity.



TEC MAT Silicon Rubber Drip Mat can be used underneath the TEC 810 gun to protect work surfaces against damage caused by molten hotmelt adhesive

