

**This Unique Driveway Monitor Sends a Wireless Signal to Your Home or Office to Alert You When a Vehicle Enters Your Driveway**

The receiver chimes and the alert light flashes when a vehicle passes by the sensor. The alert light continues to flash for 15 minutes or until the reset button is pushed. Note: When a vehicle enters your driveway and triggers the Driveway Monitor, there is a five second delay for the unit to reset before the next vehicle will be detected.

**How It Works**

The driveway sensor uses a patented magnetometer sensor system. Movement of any large metallic (iron or steel) object having a magnetic field will cause the sensor to transmit to the receiver. People, animals and shadows will not trigger the driveway sensor.

The sensor may be placed as far as 1000 feet (line of sight) away from the receiver in your home.



STI-30150

Optional Lamp  
Controller  
STI-30104**Features**

- Alerts you when a vehicle is coming up your driveway. Indoor AC-powered receiver chimes and flashes when a vehicle approaches.
- When a vehicle passes near the SENSOR, the RECEIVER chimes and flashes the alert light. The alert light will flash for 15 minutes after a vehicle is detected. The receiver will continue to chime each time a vehicle passes.
- Under ideal conditions, the sensor may be placed as far as 1000 feet (line of sight) away from the receiver in your home.
- When a vehicle activates the receiver, there is a 20-30 second delay for the sensor to reset before the next vehicle will be detected.
- Will not be triggered by animals, people or shadows.
- Purchase additional Driveway Monitor sensors or receivers to cover multiple areas and to expand your system (up to 4 sensors).
- Can be set to low, medium or high sensitivity level.
- Additional transmitter will produce a different chime from the receiver when triggered.
- Receiver has a 12 volt transistor output jack for optional accessories. Output is adequate for small 12 volt relay coil.
- Optional Lamp Controller (STI-30104) will turn on for the selected amount of time.
- Can temporarily silence the receiver (for example to avoid the 5 a.m. garbage pickup from triggering your sensor).
- Wireless frequency is 315 Mhz.

**Safety Technology International, Inc.**

2306 Airport Road • Waterford, Michigan 48327-1209

Phone: 248-673-9898 • Fax: 248-673-1246 • Toll Free: 800-888-4784 • E-mail: [info@sti-usa.com](mailto:info@sti-usa.com) • Web: [www.sti-usa.com](http://www.sti-usa.com)

Europe Branch Office • Unit 49G Pipers Road • Park Farm Industrial Estate • Redditch • Worcestershire • B98 0HU • England

Tel: 44 (0) 1527 520 999 • Fax: 44 (0) 1527 501 999 • Freephone: 0800 085 1678 (UK only) • E-mail: [info@sti-europe.com](mailto:info@sti-europe.com) • Web: [www.sti-europe.com](http://www.sti-europe.com)

# STI Battery Driveway Monitor

## STI-30150 BATTERY

- Driveway sensor (transmitter)
- Indoor receiver
- Receiver antenna
- Mounting kit for driveway sensor
- AC adapter for receiver
- 2 screws for mounting stake

## Optional Accessory

- STI-30104** Lamp Controller - will turn on a lamp anytime your Driveway Monitor is triggered
- STI-30151** Additional Driveway sensor (includes STI-30106)
- STI-30102** Additional Driveway Monitor receiver
- STI-30103** Power supply for Driveway Monitor
- STI-30105** Extended antenna
- STI-30106** Mounting Replacement Kit (includes cap, wall mount, tube and stake)

**NOTE:** 2 "C" batteries required (not included)

## NOTE

One year warranty from the date of original purchase.

